


SISALATION® MULTIPURPOSE EHD (456)

Description

Sisalation® Multipurpose EHD (456) is a flexible, non vapour permeable water barrier designed as a second skin for residential and commercial wall and roofing applications. This product is a foil based membrane with an antiglare face designed to minimise glare experienced during installation.

Product Composition



Application

Sisalation® Multipurpose EHD (456) is designed for use as a pliable building membrane in applications such as brick veneer walls, tile roofs (with the exception of slate) and metal roofs (where it can be installed under the battens). Sisalation® Multipurpose products are specifically designed for external wall applications in climate zones 1–5 and in suitable roofing applications in all climate zones.

When overlapped and sealed with Vapastop® 883 Reinforced Foil Tape, Sisalation® Multipurpose products provide a tough secondary skin for vapour and moisture control and act as a wind, heat and dust barrier. This effective barrier also protects the building frame by minimising the amount of rain and dust that penetrates.

Features and Benefits

Extra Heavy Duty product	Suitable for use in both residential and commercial projects.
Vapour and water barrier	Provides a second skin of protection from water ingress to the building.
Antiglare face	Reduces glare during installation.

Product Data

Width mm	Length m	Area per roll m ²	Weight per roll kg	Product Code
1350	30	40.50	4.66	352330
	60	81.00	9.32	352360
1500	30	45.00	5.12	352331

Physical Properties

Property	Test Method/Standard	Test Result	Unit
Duty Classification	AS 4200:1	Extra Heavy Duty	
Edge Tear	Machine	≥ 90	N
	Lateral	≥ 90	N
Tensile Strength	Machine	≥ 13.0	kN/m
	Lateral	≥ 10.5	kN/m
Vapour Control	ASTM E96	Class 1 Vapour Barrier	
Water Control	AS/NZS 4201.4	Water Barrier	
Emittance	Anti-glare face	IR Non-reflective (0.9)	
	Silver side	IR Reflective (0.03)	
Resistance to Dry Delamination	AS/NZS 4201.1	PASS	
Resistance to Wet Delamination	AS/NZS 4201.2	PASS	
Shrinkage	AS/NZS 4201.3	≤ 0.5	%
Electrical Conductivity	AS/NZS 3100	Electrically Conductive	
Nominal Thickness		< 1.0	mm

Fire Hazard Properties

Sisalatation® Multipurpose EHD (456) exhibits the following characteristics when tested in accordance with the following standards:

Property	Test Method/Standard	Result
Flammability Index	AS 1530.2	≤ 5 (Low)

Compliance

Sisalatation® Multipurpose EHD (456) products comply with the National Construction Code (NCC) for sarking type materials and satisfy the following requirements:

- AS 4200.1 for 'Pliable Building Membranes' Deemed to Satisfy Standard, recognised by NCC Volumes 1 and 2.
- NCC 2019 Volume 1 Non-Combustible building elements C1.9(e) (vi) Sarking-type materials that do not exceed 1mm in thickness and have a Flammability Index not greater than 5. NCC 2019 Volume 2 General Concession – Non-Combustible Materials 3.7.1.1 (f) Sarking-type materials that do not exceed 1mm in thickness and have a Flammability Index not greater than 5.
- Suitable for use in bushfire areas with a Bushfire Attack Level (BAL) Low to FZ (wall) or Low - 40 (roof) in accordance with AS 3959.

Environmental properties

Fletcher Insulation avoids the use of Ozone Depleting Potential (ODP) substances in the manufacture or composition of its FBS-1 Glasswool Bio-Soluble Insulation® and Sisalatation® reflective foil products.

The use of Sisalatation® pliable building membranes guarantees the use of zero ODP insulation while also ensuring that no harmful levels of Volatile Organic Compounds (VOCs) are released. This allows the incorporation of environmentally preferable insulation whilst also maintaining indoor air quality.

Important Notes

- Sisalation® pliable building membrane products must be kept dry, out of contact with direct sunlight and out of contact with alkaline products, cement and mortar as well as corrosive environments such as chlorine.
- Sisalation® pliable building membrane products are not designed to withstand weathering hence the external cladding should be applied without delay.
- Sisalation® pliable building membrane products shall be installed in accordance with AS 4200.2 'Pliable Building Membranes and Underlays – Installation Requirements for Metal Roofs, Tile Roofs and Walls'. Additional guidelines are available for download via www.insulation.com.au or by contacting Fletcher Insulation on 1300 654 444.
- Building Designer to consider the suitability of this product based on the projects design requirements.

Specification Notes

When specifying, state the following:

The wall wrap material shall be Fletcher Insulation Sisalation® Multipurpose EHD (456).

© Fletcher Insulation Pty Limited 2022. Fletcher Insulation reserves the right to change product specifications without prior notification. Information in this publication and otherwise supplied to users as to the subject product is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of products, no warranty is given or is to be implied with respect to either such information or the product itself, in particular the suitability of the product for any particular purpose. The purchaser should independently determine the suitability of the product for the intended application. The colour PINK, Pink® and Pink Batts® are registered trademarks of Owens Corning Intellectual Capital, LLC used under licence by Fletcher Insulation. FBS-1 Glasswool Bio-Soluble Insulation® is a registered trademark of ICANZ. Unless otherwise stated all ™ and ® are trademarks and registered trademarks of Fletcher Insulation Pty Limited ABN 72 001 175 355. FTDS7_Revision_8_ Issue Date 06022024.

For more information call 1300 654 444
email info@insulation.com.au or web www.insulation.com.au

